MATERIAL SAFETY DATA SHEET Page: 1 of 3

NATIONAL SANITARY SUPPLY CO. 13217 S. Figueroa Street Los Angeles, California 90061 Emergency No.1-800-535-5053 (INFOTRAC)

SECTION 1. IDENTIFICATION OF PRODUCT

-----

Product Name: VANGUARD GRAFFITI AND MARK Date Issued: 11/28/95

REMOVER GEL Supercedes: 08/02/94
Type of Product: GRAFFITI/ REMOVER National Item#: 2660XX

SECTION 2. INGREDIENTS CAS# SARA OSHA-PEL ACGIH-TLV III LIST (PPM) (PPM)

ISOPROPYL ALCOHOL 67-63-0 YES 400 400 TOLUENE 108-88-3 YES 200 100 ACETONE 67-64-1 YES 1000 750 METHANOL 67-56-1 YES 200 200 METHANOL ISOBUTANE/PROPANE BLEND 75-28-5/ NO 800 800 74-98-6 NO 1000 1000

ETHYLENE GLYCOL

N-BUTYL ETHER 111-76-2 YES 25 25

SECTION 3. PHYSICAL DATA

-----Vapor Density (air=1): NE Water Reactive: NO

Specific Gravity(H20=1)Concentrate Only:0.80 Boiling Point: N/A Solubility in Water: SOLUBLE Evaporation Rate ( ): NE Vapor Pressure, psig @ 70 F: MAX. 60 Vapor Pressure(Non-Aersols)

(mm Hg and Temperature): NA

Apperance and Odor: CLEAR GEL, AROMATIC SOLVENT ODOR.

Section 4. FIRE AND EXPLOSION HAZARD DATA

Flash Point And Method Used (non-aerosols): N/A

Auto Ignition Temperature, F: NE

Flammability as per USA Flame Projection Test(Aerosls): EXTREMELY FLAMMABLE Flammable Limits in Air, Volume %: LOWER(LEL)-NE UPPER(UEL)- NE Extinguishing Media: FOAM, DRY CHEMICAL, CARBON DIOXIDE, WATER FOG. Special Firefighting Procedures: SELF CONTAINED BREATHING APPARATUS.

Unusual Fire And Explosion Hazards: DO NOT EXPOSE AEROSOLS TO TEMPERATURES

ABOVE 130F OR THE CONTAINER MAY RUPTURE.

MATERIAL SAFETY DATA SHEET Page: 2 of 3

Product Name: VANGUARD GRAFFITI AND MARK REMOVER GEL

National Item#: #2660 Date Issued: 11/28/95

-----

SECTION 5. REACTIVITY DATA

Stability: STABLE

Conditions To Avoid: OPEN FLAME, WELDING ARCS, HEAT, SPARKS. Incompatibility - Materials to Avoid: ACIDS AND STRONG OXIDIZERS.

Hazardous Polymerization Products: WILL NOT OCCUR

Hazardous Decomposition Products: CO, CO2

-----

SECTION 6. SPILL, LEAK AND DISPOSAL PROCEDURES

-----

Steps to be Taken if Material is Spilled or Released:

ABSORB WITH SUITABLE MEDIUM. INCINERATE OR LANDFILL ACCORDING TO LOCAL, STATE, AND FEDERAL REGULATIONS. PREVENT FROM ENTERING DRAINS AND SEWER. Waste Disposal Methods: AEROSOL CANS WHEN VENTED TO ATMOSPHERIC PRESSURE THROUGH NORMAL USE, POSE NO DISPOSAL HAZARD.

Precautions to be Taken in Handling and Storage: DO NOT PUNCTURE OR INCINERATE CONTAINERS. DO NOT STORE AT TEMPERATURES ABOVE 130F.

Other Precautions and / or Special Hazards: AVOID FOOD CONTAMINATION.

KEEP OUT OF REACH OF CHILDREN. REMOVE IGNITION SOURCES. AVOID BREATHING VAPORS.

-----

## SECTION 7. HEALTH HAZARD DATA

\_\_\_\_\_\_

Primary Route(s) of Entry: INHALATION, SKIN ABSORPTION

Acute Effects:

Inhalation: EXCESSIVE INHALATION OF VAPORS CAN BE HARMFUL AND MAY CAUSE HEADACHE, DIZZINESS, ASPHYXIS, ANESTHETIC EFFECTS AD POSSIBLE UNCONSCIOUSNESS.

Eye Contact: IRRITATION Skin Contact: IRRITATION

Ingestion: POSSIBLE CHEMICAL PNEUMONITIS IF ESPIRATED INTO LUNGS. NAUSEA. Chronic Effects: (EFFECTS DUE TO EXCESSIVE EXPOSURE TO THE RAW MATERIALS OF THIS MIXTURE) MAY CAUSE CARDIAC ABNORMALITY, LIVER ABNORMALITIES, KIDNEY AND/OR LIVER DAMAGE. LAB ANIMALS HAVE EXPERIENCED ANEMIA, LIVER, KIDNEY, LUNG, BLOOD DAMAGE TO GLYCOL ETHER EB.

Medical Conditions Generally Aggravated by Exposure: MAY AGGRAVATE EXISTING EYE, SKIN, OR UPPER RESPIRATORY CONDITIONS.

MATERIAL SAFETY DATA SHEET Page: 3 of 3

Product Name: VANGUARD GRAFFITI AND MARK REMOVER GEL

National Item#: #2660 Date Issued: 11/28/95

\_\_\_\_\_

## SECTION 8. EMERGENCY AND FIRST AID PROCEDURES

-----

Eye Contact: FLUSH WITH WATER FOR 15 MINUTES. IF IRRITATED, SEEK MEDICAL ATTENTION.

Skin Contact: WASH WITH SOAP AND WATER. IF IRRITATED, SEEK MEDICAL ATTENTION.

Inhalation: REMOVE TO FRESH AIR. RESUSCITATE IF NECESSARY. GET MEDICAL ATTENTION.

Ingestion: DO NOT INDUCE VOMITING. DRINK TWO LARGE GLASSES OF WATER. GET IMMEDIATE MEDICAL ATTENTION.

-----

## SECTION 9. CONTROL AND PROTECTIVE MEASURES

Respiratory Protection: IF VAPOR CONC. EXCEEDS TLV, USE RESPIRATOR APPROVED BY U.S. BUREAU OF MINES FOR ORGANIC VAPOR.

Protective Gloves: RUBBER GLOVES.

Eye Protection: SAFETY GLASSES RECOMMENDED.

Ventilation Requirements: ADEQUATE VENTILATION TO KEEP VAPOR CONCENTRETION

BELOW TLV.

Other Protective Clothing and Equipment: NONE

Hygienic Work Practices: WASH WITH SOAP AND WARM WATER BEFORE HANDING FOOD.

REMOVE CONTAMINATED CLOTHING.

-----

SECTIION 10. ADDITIONAL INFORMATION

-----

SARA TITLE III H&P RATING: Acute: YES Chronic: YES Fire: YES
Press. Relese: NO Reactive: NO

HMIS RATING: HEALTH -2 FLAMMABILITY - 4 REACTIVITY - 0 PERSONAL - B

NFPA RATING: HEALTH -2 FLAMMABILITY - 4 REACTIVITY - 0 SPECIAL - 0

\*Warning: THIS PRODUCT MAY CONTAIN DETECTABLE AMOUNTS OF SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER OR REPRODUCTION RISK.

THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET REPRESENTS THE LATEST DATA AND BEST OPINION AS TO THE PROPER USE AND HANDLING OF THIS PRODUCT UNDER NORMAL CONDITIONS. ANY USE OF THIS PRODUCT OR METHOD OF APPLICATION WHICH IS NOT IN CONFORMANCE WITH THIS DATA SHEET AND THE PRODUCT LABEL DIRECTIONS, IS THE RESPONSIBILITY OF THE USER. THIS MATERIAL SAFETY DATA SHEET WAS PREPARED TO COMPLY WITH THE OSHA HAZARD COMMUNICATION REGULATION.

-----