

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND DISTRIBUTOR'S INFORMATION						
NFPA Rating: Health-2; Flammability-3; Reactivity-0; Special- -			HMIS Rating: Health-2; Flammability-3; Reactivity-0; Personal Protection-B			
Manufactured For: UNISOURCE WORLDWIDE, INC. Address: 6600 Governors Lake Pkwy. Norcross, GA 30071			DOT Hazard Classification: ORM-D Identity (trade name as used on label): ALLSTAR VANGUARD (U17532)			
Phone: 800-UNISOURCE			MSDS Number: A00179 Revision - 17			
EMERGENCY RESPONSE NUMBER: 1-888-660-6737			Information Calls: (770)422-2071			
NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA			Date Prepared: 12/06/01 Prepared By: CH/IB			
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION						
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)		CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **
ETHYL ALCOHOL		64-17-5	No	1000	1000	d
TOLUENE		108-88-3	Yes	200	100	d
ACETONE		67-64-1	No	1000	750	d
ISOPROPYL ALCOHOL		67-63-0	No	400	400	d
2-BUTOXYETHANOL *		111-76-2	Yes	25 (skin)	20 (skin)	d
ISOBUTANE / PROPANE BLEND		75-28-5	No	800	800	d
		74-98-6	No	1000	1000	d
METHANOL		67-56-1	Yes	200	200	d
*GLYCOL ETHER						
WARNING: This product contains a chemical or chemicals known to the State of California to cause birth defects or other reproductive harm.						
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS						
Boiling Point: N/A		Specific Gravity (H2O=1): Concentrate Only = 0.81				
Vapor Pressure: PSIG @ 70°F (Aerosols): Max.60		Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A				
Vapor Density (Air = 1): N/E		Evaporation Rate (= 1): N/E				
Solubility in Water: Soluble		Water Reactive: No				
Appearance and Odor: Clear gel, aromatic solvent odor.						
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA						
FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols) EXTREMELY FLAMMABLE		Auto Ignition Temperature N/E	Flammability Limits in Air by % in Volume: % LEL: N/E % UEL: N/E			
FLASH POINT AND METHOD USED (non-aerosols): N/A		EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water fog.				
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.						
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.						
SECTION 4 - REACTIVITY HAZARD DATA						
STABILITY [X] STABLE [] UNSTABLE		HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR				
Incompatibility (Mat. to avoid): Acids and strong oxidizers.		Conditions to Avoid: Open flame, welding arcs, heat, sparks.				
Hazardous Decomposition Products: CO, CO2.						
SECTION 5 - HEALTH HAZARD DATA						
PRIMARY ROUTES OF ENTRY: [X] INHALATION [] INGESTION [X] SKIN ABSORPTION [] EYE [] NOT HAZARDOUS						
ACUTE EFFECTS:						
Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.						
Eye Contact: Irritation		Skin Contact: Irritation				
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.						
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) May cause cardiac abnormality, liver abnormalities, kidney and/or liver damage. Lab animals have experienced anemia, liver, kidney, lung, blood damage to Glycol Ether EB.						
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.						
EMERGENCY FIRST AID PROCEDURES						
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.						
Skin Contact: Wash with soap and water. If irritated, seek medical attention.						
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.						
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.						
SECTION 6 - CONTROL AND PROTECTIVE MEASURES						
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by U.S. Bureau of Mines for organic vapor.						
Protective Gloves: Rubber gloves.		Eye Protection: Safety glasses recommended.				
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.						
Other Protective Clothing & Equipment: None						
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.						
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE						
Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or Federal regulations. Prevent from entering drains and sewer.						
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.						
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.						
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors. Remove ignition sources.						

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only

SAP# 1020454