Maint Shop

AGS COMPANY

## **PAGE 59**

Lith-Ease Grease

# MATERIAL SAFETY DATA SHEET

Product	t:	WL-1, WL-14, WL-15, WL-15BK, WL-19 WL-1H, WL-2BK, WL-35, WL-8, WLB-1, WLC-1			Trade Name:		Lith-Ease Grease			
Manufac		AGS Company	y	K, WL-35, WL-8, WLB-1, WLC-1		Common Name:		White Lithium Grease		
Street A		2651 Hoyt S								
City/Sta Phone:	te/Zip	Muskegon Ht								
Phone:		800-253-040								
Phone: 231-733-2101   FAX: 231-733-1784   Transportation Emergency: CHEM-TEL				Original Ise		Date	11/12/1985 12/10/2012			
			54		Revision No 13					
Phone:	tation Energence	800-255-392	24							
			CTION 2 - COMPOS				NTO			
		UL	0110112-00111-00		MATION UN	INGREDIE	INTS			
ITEM					CAS NUMB	ER	WT/WT	%		
	1 Mineral Oil				64742-65-0	)	60-100			
	2 Mineral Oil				64742-52-5	5	15-40			
			roxy-, monolithium s	əlt	7620-77-1	l	5-10			
	4 Calcium Ca				471-34-1		3-7			
	5 Fillec 350 (E	tnyi Corporatio	thyl Corporation)			Proprietary		1-5		
			EXPOSURE LIM	ITS						
	ACGIH				OSHA					
TEM	TLV-TWA	-	PEL-TWA							
	1 5	5 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>		mg/m <sup>3</sup>	N.E.				
	2 5	5 mg/m <sup>3</sup>	$10 \text{ mg/m}^3$		mg/m <sup>3</sup>	N.E.				
	3 N.E		N.E.	N.E.	mg/m	N.E.				
	4 10	) mg/m3			mg/m3	5 mg/m3 i		fraction		
	5 N.E.		N.E.	N.E.	ing/ino	N.E.		maction.		
			(See Sect	ion 16 for abbre	eviation leger					
			SECTION 3	- HAZARDS ID	ENTIFICATI	ON				
EYE CON	ITACT:	May be irritatir	ng and can cause pa	in, tearing, redo	lening and s	welling.				
SKIN CO	NTACT:	Prolonged or r	repeated contact may	result in irritat	ion and/or de	ermatitis.				
NHALAT	ION:	Prolonged inha	alation may cause he	adaches, dizzi	ness and nai	usea.				
NGESTION: This material may be harmful if swallowed.				allowed.						
CHRONIC HAZARDS: There are no foreseeable uses of the produ			ne product that	would lead t	o chronic e	xposure.				
rimary R	oute(s) of Entry	Skin and eye c	contact or ingestion.							
			OFOTION	4 - FIRST AID						

SKIN CONTACT: Immediately flush with plenty of water. Remove clothing. Get medical attention immediately. Wash clothing separately before reuse.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

INGESTION: Get medical attention immediately. If swallowed, DO NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

#### AGS COMPANY

## **PAGE 59**

#### MATERIAL SAFETY DATA SHEET SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT:	440°F			JPPER EXPL			N.A. N.A.	% %		
AUTOGNITION TEMPER	ATURE:	490°F								
EXTINGUISHING MEDIA: Wa		Water fog	Nater fog, dry chemical, CO <sup>2</sup> , foam, and alcohol foam							
UNUSUAL FIRE AND EXP	Product can produce dense smoke from oils burning.									
SPECIAL FIREFIGHTING PROCEDURES: protective gear.			Wear NIOSH/MSHA approved self-contained breathing apparatus and							
		SECT	ION 6 - ACCIDE	ENTAL RELEA	SE MEASUR	ES				
RECOVERY PROCEDURES: Scrape up material and place in a chemical waste container.										
		S	ECTION 7 - HA		STORAGE					
HANDLING: Wash thoroughly after handling										

STORAGE: Keep away from heat, sparks, and flame.

#### SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: No special controls needed when used in supplied form.

RESPIRATORY PROTECTION: For most conditions, no respiratory protection should be needed, however, if high vapor concentration should develop, use a NIOSH approved organic vapor respirator.

SKIN PROTECTION: Where contact is likely, wear chemical resistant gloves.

EYE PROTECTION: Wear safety glasses with side shields or goggles.

OTHER PROTECTIVE EQUIPMENT: Eye wash in work area.

HYGIENIC PRACTICES: Wash hands before eating. Remove contaminated clothing and wash before reuse. Use only in a well ventilated area. Follow all MSDS/label precautions even after container is emptied because they may retain product residues. Avoid prolonged or repeated contact with eyes, skin, and clothing.

#### SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE ODOR APPEARANCE SOLUBILITY IN H₂O	700°F Petroleum Cream Color Negligible	VAPOR DENSITY: ODOR THRESHOLD EVAPORATION RATE	Is heavier than air N.D. Is slower than Butyl Acetate				
FREEZE POINT	N.D. N.D.	SPECIFIC GRAVITY pH @ 0.0%	0.88-0.9 N.A.				
VAPOR PRESSURE PHYSICAL STATE	Grease/semi-solid	VISCOSITY:	N.D.				
COEFFICIENT OF WATER / OIL DISTRIBUTION: Negligible							

## MATERIAL SAFETY DATA SHEET SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID: Sources of ignition.

INCOMPATIBILITY: Strong acid or alkali, oxidizers and amines.

HAZARDOUS DECOMPOSITION PRODUCTS Oxides of carbon and nitrogen.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions

STABILITY: This product is stable under normal storage conditions.

SECTION 11 - TOXICOLOGICAL PROPERTIES									
PRODUCT I	LD-50	N.D.	PRODUCT	LC-50	N.D.				
COMPONEN	T TOXICOLOGICAI		۷:						
(	CHEMICAL NAME			LD50	LC	C50			
SECTION 12 - ECOLOGICAL INFORMATION									
ECOLOGICAL	LINFORMATION:	No inform	nation						
SECTION 13 - DISPOSAL CONSIDERATIONS									
DISPOSAL METHOD: Dispose of in accordance with federal, state and local regulations.									
SECTION 14 - TRANSPORTATION INFORMATION									
DOT PROPER	R SHIPPING NAME	Not Regu	lated						
DOT TECHNIC	CAL NAME								
DOT HAZARD	CLASS		HAZARD SUBCLASS: N.A.						
DOT UN / NA	NUMBER:		PACKING G	RESP. GUIDE	PAGE				
SECTION 15 - REGULATORY INFORMATION									
U.S. FEDERAL	REGULATIONS:	AS FOLL	OWS -						

U.S FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 cfr 1910.1200)

CERCLA - SARA HAZARD CATEGORY:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III ) and is considered, under applicable definitions, to meet the following categories:

	MATERIAL SAFETY DATA SHEET								
SARA SECTION 313 This product contains the following substance subject to the reporting requirements of Section 313 of Title of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:									
CHEMICA No SARA Section 313		tist in this p	product.	CAS NUN	IBER	WT /WT	% IS LES	S THAN %	
TOXIC SUBSTANCE CONTROL ACT: This product contains the following chemical substances subject to the reporting requirements of TSCA 12 (B) if exported from the United States:									
CHEMICA There are no compone		SCA 12(b)	)	CAS NUN	IBER				
U.S. STATE REGULAT	IONS:	AS FOL	LOWS -						
NEW JERSEY RIGHT- The following materials		dous, but a	are among the to	op five com	ponents in th	is product:	:		
CHEMICAL NAME CAS NUMBER No non-hazardous materials are among the top five ingredients.									
PENNSYLVANIA RIGH The following non-haza		nts are pre	sent in the prod	uct at grea	ter than 3%:				
CHEMICAL NAME CAS NUMBER No non-hazardous ingredients are present at greater than 3%.									
CALIFORNIA PROPOS WARNING: The chem to causes cancer, birth	ical(s) noted be			product, ai	re know to the	e state of C	California		
CHEMICA No Propsition 65 chemi		s product.		CAS NUN	IBER				
INTERNATIONAL REG	ULATIONS:	AS FOL	LOWS -						
CANADIAN WHMIS: except for use of the 16		has been	prepared in con	npliance wi	th Controlled	Product R	egulations	3	
CANADIAN WHMIS CL	ASS:	No inform	mation available						
			SECTION 16	- OTHER	INFORMATIC	DN			
HMIS RATINGS: NFPA	Health Health	0 0	Flammability Flammability		Phys. Haz. Reactivity	0 0	PPE	А	

# **PAGE 59**

Disclaimer: The information contained herein is base on data available. However, no warranty is expressed or implied regarding the accuracy of the data or the results obtained from the use thereof. Because the information contained herein may be applied under conditions beyond our control, we assume no responsibility for its use.

N.E.

VOLATILE ORGANIC COMPOUNDS (VOCs):

Not Applicable

Not Determined

N.A.

N.D.

LEGEND:

0 lbs/gal

Not Established

0 grams / liter